

UKKO SERIES

CARACTERISTIQUES TECHNIQUES

MODELE	LARGEUR TRAVAIL	DISQUES	DISQUES 26" / 660x6mm.		
			LARGEUR TRANSPORT	PUISSANCE	POIDS APPROX.
"RTR"	M.	Nº	mm.	HP/CV	Kg.
GR-RTR206 - 18	2,06	18	2320	70-80	1650
GR-RTR230 - 20	2,30	20	2560	80-90	1750
GR-RTR254 - 22	2,54	22	2800	90-100	1850
GR-RTR278 - 24	2,78	24	3040	100-110	1950
GR-RTR302 - 26	3,02	26	3280	115-130	2050
GR-RTR326 - 28	3,26	28	3520	130-140	2150
GR-RTR350 - 30	3,50	30	3760	140-150	2250
GR-RTR374 - 32	3,74	32	4000	150-160	2350
GR-RTR398 - 34	3,98	34	4240	160-170	2450
GR-RTR422 - 36	4,22	36	4480	170-180	2550

SECTION CHASIS: 180x100x8 mm.
 DISQUES: 26" / 660x6 mm.
 ESPACEMENT INTER DISQUES: 240 mm.
 PROFONDEUR MAX.: 250 mm.
 Nº PALIERS: 8 (12: 34/36 DISQUES)
 PNEUS: 10.0/75-15,3"

M T O D U E S L E S	CATEGORIE: II TRANSPORT EN LONG: 2800 mm.
--	--

MODELE	LARGEUR TRAVAIL	DISQUES	DISQUES 28" / 710x6mm.		
			LARGEUR TRANSPORT	PUISSANCE	POIDS APPROX.
"RTR"	M.	Nº	mm.	HP/CV	Kg.
GR-RTR208 - 16	2,08	16	2290	80-90	1850
GR-RTR235 - 18	2,35	18	2560	90-100	2020
GR-RTR262 - 20	2,62	20	2830	100-110	2150
GR-RTR289 - 22	2,89	22	3100	110-120	2280
GR-RTR316 - 24	3,16	24	3370	120-130	2410
GR-RTR343 - 26	3,43	26	3640	130-140	2540
GR-RTR370 - 28	3,70	28	3910	140-150	2670
GR-RTR397 - 30	3,97	30	4180	150-160	2800
GR-RTR424 - 32	4,24	32	4450	170-180	2920

SECTION CHASIS: 200x100x10 mm.
 DISQUES: 28" / 710x6 mm.
 ESPACEMENT INTER DISQUES: 270 mm.
 PROFONDEUR MAX.: 275 mm.
 Nº PALIERS: 8 (12: 30/32 DISQUES)
 PNEUS: 11.5/80 - 15,3"





UKKO SERIES

CARACTERISTIQUES TECHNIQUES

DISQUES 26" / 660x6mm.					
MODELE	LARGEUR TRAVAIL	DISQUES	LARGEUR TRANSPORT	PUISSANCE	POIDS APPROX.
"RTN"	M.	Nº	mm.	HP/CV	Kg.
GR-RTN182 - 16	1,82	16	2070	60	1350
GR-RTN206 - 18	2,06	18	2310	70	1450
GR-RTN230 - 20	2,30	20	2550	80	1550
GR-RTN254 - 22	2,54	22	2790	90	1650
GR-RTN278 - 24	2,78	24	3030	100	1750
GR-RTN302 - 26	3,02	26	3270	115	1850
GR-RTN326 - 28	3,26	28	3510	130	2000

SECTION CHASIS: 180x100x8 mm.
 DISQUES: 26" / 660x6 mm.
 ESPACEMENT INTER DISQUES: 240 mm.
 PROFONDEUR MAX.: 250 mm.
 Nº PALIERS: 8
 PNEUS: 10.0/80 - 12"
 CATEGORIE: II



Gascón International
 Herederos de Manuel Gascón S.L.
 Tel. +34-974-21 87 20
 Fax. +34-974-21 87 21

info@hmgascon.com

INTERNATIONAL OFFICES
 Tel. +34-689 82 30 51
 Tel.Fax. +34-93-783 87 93

export@hmgascon.com

UKKO SERIES

CARACTERISTIQUES TECHNIQUES

MODELE	LARGEUR TRAVAIL	DISQUES	LARGEUR TRANSPORT	DISQUES 26" / 660x6mm.	
				PUISSANCE	POIDS APPROX.
RTSE	M.	Nº	mm.	HP/CV	Kg.
GR-RTSE206 - 18	2,06	18	2450	70-80	1700
GR-RTSE230 - 20	2,30	20	2690	80-90	1800
GR-RTSE254 - 22	2,54	22	2930	90-100	1900
GR-RTSE278 - 24	2,78	24	3170	100-110	2000
GR-RTSE302 - 26	3,02	26	3410	115-130	2100
GR-RTSE326 - 28	3,26	28	3650	130-140	2200
GR-RTSE350 - 30	3,50	30	3890	140-150	2300
GR-RTSE374 - 32	3,74	32	4130	150-160	2400
GR-RTSE398 - 34	3,98	34	4370	160-170	2500

SECTION CHASIS: 180x100x8 mm.
 DISQUES: 26" / 660x6 mm.
 ESPACEMENT INTER DISQUES: 240 mm.
 PROFONDEUR MAX.: 250 mm.
 Nº PALIERS: (4> de 18 à 24 discos) (6> de 26 à 34)
 PNEUS: 10.0/75-15,3"

M T O D U E S L E S	CATEGORIE: II
	TRANSPORT EN LONG: 2800 mm.

MODELE	LARGEUR TRAVAIL	DISQUES	LARGEUR TRANSPORT	DISQUES 28" / 710x6mm.	
				PUISSANCE	POIDS APPROX.
"RTSE"	M.	Nº	mm.	HP/CV	Kg.
GR-RTSE181 - 14	1,81	14	2180	70-80	1880
GR-RTSE208 - 16	2,08	16	2450	80-90	1950
GR-RTSE235 - 18	2,35	18	2720	90-100	2120
GR-RTSE262 - 20	2,62	20	2990	100-110	2250
GR-RTSE289 - 22	2,89	22	3260	115-130	2380
GR-RTSE316 - 24	3,16	24	3530	130-140	2510
GR-RTSE343 - 26	3,43	26	3800	140-150	2640
GR-RTSE370 - 28	3,70	28	4070	150-160	2770
GR-RTSE397 - 30	3,97	30	4340	160-170	2900
GR-RTSE424 - 32	4,24	32	4610	170-180	3020

SECTION CHASIS: 200x100x10 mm.
 DISQUES: 28" / 710x6 mm.
 ESPACEMENT INTER DISQUES: 270 mm.
 PROFONDEUR MAX.: 275 mm.
 Nº PALIERS: (4> de 14 à 22 discos) (6> de 24 à 34)
 PNEUS: 11.5/80 - 15,3"



UKKO SERIES

CARACTERISTIQUES TECHNIQUES

MODELE	LARGEUR TRAVAIL	DISQUES	LARGEUR TRANSPORT	DISQUES 32" / 810x10mm.	
				PUISSANCE	POIDS APPROX.
"RTSD"	M.	Nº	mm.	HP/CV	Kg.
GR-RTSD220 - 14	2,20	14	2530	120-130	3250
GR-RTSD250 - 16	2,50	16	2830	130-140	3400
GR-RTSD280 - 18	2,80	18	3130	140-150	3550
GR-RTSD310 - 20	3,10	20	3430	150-160	3700
GR-RTSD340 - 22	3,40	22	3730	160-170	3850
GR-RTSD370 - 24	3,70	24	4030	170-180	4000
GR-RTSD400 - 26	4,00	26	4330	180-190	4150
GR-RTSD430 - 28	4,30	28	4630	190-200	4300

SECTION CHASIS: 300x150x12 mm.
 DISQUES: 32" / 810x10 mm.
 ESPACEMENT INTER DISQUES: 320 mm.
 PROFONDEUR MAX.: 300 mm.
 Nº PALIERS: 8
 PNEUS: >265/70R19> de 14 à 22 disques
 >285/70R19> de 24 à 28 disques
 CATEGORIE: II

MODELE	LARGEUR TRAVAIL	DISQUES	PALIERS	LARGEUR TRANSPORT	DISQUES 36" /	
					PUISSANCE	
"RTD"	M.	Nº	Nº	mm.	HP/CV	
GR-RTD250 - 12	2,50	12	4	2885	170-180	
GR-RTD290 - 14	2,90	14	8	3285	180-190	
GR-RTD330 - 16	3,30	16	8	3685	190-200	
GR-RTD370 - 18	3,70	18	8	4085	200-210	
GR-RTD410 - 20	4,10	20	8	4485	210-220	
GR-RTD450 - 22	4,50	22	8	4885	220-230	
GR-RTD490 - 24	4,90	24	12	5285	230-240	

SECTION CHASIS: 500x185x20 mm.
 DISQUES: 36" / 910x12 mm.
 ESPACEMENT INTER DISQUES: 400 mm.
 PROFONDEUR MAX.: 300 mm.
 PNEUS: 285/70R19
 CATEGORIE: III

